



Floor standing unit

FVXS-F



Guaranteed operation down to -25°C



Econo mode



Vertical auto swing



Weekly timer



Online controller via app

Floor standing unit for optimal heating comfort thanks to dual airflow, even at ambient temperatures **down to -25°C**

- › Its low height enables the unit to fit perfectly beneath a window
- › Can be installed against a wall or recessed
- › Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- › Online controller (optional): control your indoor unit from any location with an app, via your local network or internet

- › Guaranteed heating capacity at low ambient temperature, down to -25°C
- › Thanks to the unique free hanging coil technology, the defrost cycle is improved, resulting in lower running costs and no ice buildup

FVXS-F + RXL-M3



Indoor unit		FVXS	25F	35F
Casing	Colour		White	
Dimensions	Unit	HeightxWidthxDepth	mm	
			600x700x210	
Sound power level	Cooling/Heating		52/52	
Sound pressure level	Cooling	High/Nom./Low/Silent operation	38/32/26/23	39/33/27/24
	Heating	High/Nom./Low/Silent operation	38/32/26/23	39/33/27/24
Control systems	Infrared remote control		ARC452A1	


Efficiency data		FVXS + RXL	25F + 25M3	35F + 35M3	
Cooling capacity	Min./Nom./Max.	kW	1.2/2.5/5.1	1.4/3.5/5.6	
Heating capacity	Min./Nom./Max.	kW	1.0/4.5/6.5 / 3.4 (1)	1.1/5.6/7.0 / 3.8 (1)	
Power input	Cooling	Min./Nom./Max.	0.250/0.740/1.920	0.250/1.070/2.120	
	Heating	Min./Nom./Max.	0.250/1.190/2.330	0.250/1.620/2.650	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A		
		Pdesign	2.50	3.50	
		SEER	5.10	5.21	
	Heating (Average climate)	Annual energy consumption	kWh	173	235
		Energy label	A+		
		Pdesign	3.20	3.60	
		SCOP	4.04	3.80	
Heating (Cold climate)	Annual energy consumption	kWh	1,109	1,326	
	SCOP		3.41	3.10	
Nominal efficiency	EER		3.38	3.27	
	COP		3.78	3.46	
	Annual energy consumption	kWh	370	535	
	Energy label	Cooling/Heating	A/A		

Outdoor unit		RXL	25M3	35M3
Dimensions	Unit	HeightxWidthxDepth	mm	
			550x858x330	
Sound power level	Cooling		61	
	Heating		61	
Sound pressure level	Cooling	High/Low	48/44	
	Heating	High/Low	49/45	
Operation range	Cooling	Ambient	Min.-Max.	°CDB
				-10~46
Refrigerant	Heating	Ambient	Min.-Max.	°CWB
				-25~18
Type/GWP	R-410A/2,087.5			
	Charge	kg/TCO ₂ eq	1/2.1	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240	

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load
 (1) Maximum heating capacity at -15°C outdoor temperature

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-033 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.